

## Recondition Unit

### Applications:

The Recondition Unit is a multifunctional filter for absorption filtration. Depending on the contamination, different types of absorbent can be used in the Recondition Unit.

This filter is portable: it can be deployed anywhere, very quickly.

### Description rental recondition unit:

#### A. Specifications Filter Unit:

2 Filter houses of 600L	
1 Candle filter	
Connections:	4 Inch
Maximum hydraulic flow:	+/- 20 M <sup>3</sup> /hour
Design press:	10 Bar
Design temp:	40 °c
Filter medium:	
Length:	1,3 M
Height:	2 M
Width:	1,3 M
Materials:	1,4571 SS316



#### B. Spare parts:

Mano meter  
Gaskets  
Flexible hoses  
Valves

#### C. AQ vacuum unit

For filling and emptying filter house.

#### Handling guidelines for use of hose(s)

- \* To avoid any damage to the hose(s), the use of the supplied hose sling is mandatory.
- \* After use, the lessee is obliged to return hose(s) to the supplier product free and with the blind flags mounted.

#### Terms & conditions:

- \* The lessee and his representative shall safeguard the lessor from all claims arising from but not limited to damages, losses to equipment / environment / cargo / vessel during rental period.
- \* All activities are carried out under our General Terms & Conditions.
- \* Our General Terms & Conditions can be consulted at <http://www.aqnv.com>